

Claims:

- 175 1. [currently amended] A golf club head, said club head further including a
hosel extending generally upwardly from the heel end thereof and defining a
generally upwardly open hosel bore, said hosel having at least one
reinforcement bridge of material extending out from the hosel to the main
body of the club, creating a roughly cylindrical space underneath the
180 reinforcement bridge of either no material or a less structurally sound material
than that of the reinforcement bridge, wherein said club head comprises a
wood-type club head in which the hosel reinforcement bridge extends from
the hosel to the upper surface of the club head, wherein said bridge forms a
protrusion from said upper surface with said space extending higher than said
185 upper surface.
2. [withdrawn] The golf club head of claim 1 wherein said club head comprises a
wood-type club head in which the hosel reinforcement bridge extends from
the hosel to the upper surface of the club head.
3. [withdrawn] The golf club head of claim 1 wherein said club head comprises
190 an iron-type club head in which the hosel reinforcement bridge extends from
the hosel to the heel of the club head.
4. [withdrawn] The golf club head of claim 1 wherein said club head comprises a
putter-type club head in which the hosel reinforcement bridge extends from
the hosel to the heel of the club head.

- 195 5. [currently amended] A golf club, said club head further including a hosel
extending generally upwardly from the heel end thereof and defining a
generally upwardly open hosel bore, said hosel having at least one
reinforcement bridge of material extending out from the hosel to the main
body of the club, creating a roughly cylindrical space underneath the
200 reinforcement bridge of either no material or a less structurally sound material
than that of the reinforcement bridge, wherein said club head comprises a
wood-type club head in which the hosel reinforcement bridge extends from
the hosel to the upper surface of the club head, wherein said bridge forms a
protrusion from said upper surface with said space extending higher than said
205 upper surface.
6. [withdrawn] The golf club of claim 1 wherein said club head comprises a
wood-type club head in which the hosel reinforcement bridge extends from
the hosel to the upper surface of the club head.
7. [withdrawn] The golf club of claim 1 wherein said club head comprises an
210 iron-type club head in which the hosel reinforcement bridge extends from the
hosel to the heel of the club head.
8. [withdrawn] The golf club of claim 1 wherein said club head comprises a
putter-type club head in which the hosel reinforcement bridge extends from
the hosel to the heel of the club head.

- 215 9. [withdrawn] A method for designing a golf club hosel reinforcement bridge in which characteristics of the target golfer or group of golfers' swings are used to tailor the shape of the hosel reinforcement bridge and the hollow area underneath it.

220